

Technical info

Querkus – Oak Vintage



1	DESCRIPTION
---	-------------

Type: Panels: top layer (A quality with the chosen look, thickness and touch), MDF core and a balancing layer (A, B⁺ or B quality). Flex: top layer (A quality) and paper layer. The Oak vintage look uses old timbers which are recycled to retain the authentic nature.

Thickness: MDF panels: 18 mm, veneer: 1 or 1.5 mm^(*)

Splicing method: Mixmatch assembled, not spliced.

Finishing Product: Look, Thickness and Touch are free to choose according to the design. Overview of the possibilities, you can find in the brochure.

More info: www.querkusdecospan.com

	TEST METHOD	PANELS
Dimensions		3050x1220x19 or 2500x1240x19 mm
Density	EN323	600-700 kg/m ³
Moisture content panel	EN322	6 % (tolerance: ± 3)
Internal bond	EN319	≥ 0,35 N/mm ²
Bending strength	EN310	≥ 13 N/mm ²
Modulus of elasticity	EN310	≥ 1600 N/mm ²
Formaldehyde	EN171-1	≤ 0,013g/m ³
Deviation of thickness	EN14323	± 0,2 mm
Deviation of length + width	EN14323	± 2 mm
Deviation of squareness	EN324	± 2 mm/m
Flatness	EN14323	2 mm/m
VOC loss	EN664	≤ 3% ppm
PCP content	CEN14823	≤ 5 %
Fire classification	EN13501-1	D-s2

^(*)Keep in mind that this is the thickness of the veneer before we process it. The final thickness may vary.

 a product of Decospan <small>RESISTANT ABOUT WOOD VENEER</small>	Querkus – Oak Vintage	DOC code: DECO TI - 16002	
	Version 1.0	11/05/2016	Page: 1